

11. REFERENCIAS

- [1] Abhat A. (1983). Low temperature latent heat thermal energy storage: Heat storage materials. *Solar Energy*; 30:313–32.
- [2] Hawes D.W., Feldman D., Banu D. (1993). Latent heat storage in building materials. *Energy and Buildings* 20, 77–86.
- [3] Dincer I., Rosen M.A. (2002) *Thermal energy storage, systems and applications*. John Wiley & Sons, Chichester, England (2002).
- [4] Mehling H., Cabeza C. *Heat and cold storage with PCM. An up to date introduction into basics and applications*. Ed. Springer-Verlag Berlin Heidelberg, 2008.
- [5] Ip K.C.W., Gates J.R. (2000). Thermal storage for sustainable dwellings. In: *Proceedings of International Conference Sustainable Building*. Maastricht, The Netherlands.
- [6] Paris J., Falardeau M., Villeneuve C. (1993). Thermal storage by latent heat: a viable option for energy conservation in buildings. *Energy Sources*; 15:85–93.
- [7] Zalba B., Marin J.M., Cabeza L.F., Mehling H. (2003). Review on thermal energy storage with phase change materials, heat transfer analysis and applications. *Applied Thermal Engineering*; 23(3):251–83.
- [8] Telkes M. (1975). Thermal storage for solar heating and cooling. In: *Proceedings of the workshop on solar energy storage subsystems for the heating and cooling of buildings*. Charlottesville, VA, USA.
- [9] Lane G.A. (1986). *Solar heat storage: latent heat material, vol. II, technology*. Florida: CRC Press.
- [10] Sharma S.D., Sagara K. (2005). Latent heat storage materials and systems: a review. *International Journal of Green Energy*, 2: 1–56.
- [11] Khudhair A.M., Farid M.M. (2004). A review on energy conservation in building applications with thermal storage by latent heat using phase change materials. *Energy Conversion and Management* 45, 263–275.
- [12] Lane G.A. (1983). *Solar Heat Storage: Latent Heat Material. Volume I: Background and Scientific Principles*. CRC Press, Florida.
- [13] Barkmann H.G., Wessling F.C. (1975) Use of buildings structural components for thermal storage, *Proceedings of the Workshop on Solar Energy Storage Subsystems for the Heating and Cooling of Buildings*, Charlottesville (Virginia, USA).
- [14] Wada T., Yokotani F., Matsuo Y. (1984). Equilibria in the aqueous ternary system containing Na^+ , CH_3CO_2^- and $\text{P}_2\text{O}_7^{4-}$ between 38 and 85 °C. *Bull Chem Soc Jpn*; 57:1671–2.
- [15] Hauer A., Mehling H., Schossig P., Yamaha M., Cabeza L.F., Martin V., Setterwall F. *International Energy Agency Implementing Agreement on Energy Conservation through energy storage. Annex 17 Final Report* (2005).
- [16] Peippo K., Kauranen P., Lund P.D. (1991). A multi-component PCM wall optimized for passive solar heating. *Energy and Buildings* 17, 259–270.
- [17] www.micronal.de
- [18] Lorsch H.G., Kauffman K.W., Denton J.C. (1976). Thermal energy storage for heating and air conditioning, future energy production system. *Heat Mass Transfer Proc.* 1, 69–85.
- [19] Farid M.M., Khudhair A.M., Razack S.A.K., Al-Hallaj S. (2004). A review on phase change energy storage: materials and applications. *Energy Conversion and Management* 45, 1597–1615.
- [20] Paksoy H.Ö. (ed). *Thermal Energy Storage for Sustainable Energy Consumption. Fundamentals, Case Studies and Design*. NATO Science Series. 2007 Springer.
- [21] Hawes D.W., Feldman D., Banu D. Latent heat storage in building materials. *Energy and Buildings*, 20 (1993) 77–86.(esta repetido , es es numero [2])
- [22] Kenisarin M., Mahkamov K. (2007). Solar energy storage using phase change materials. *Renewable and Sustainable Energy Reviews* 11, 1913–1965.
- [23] Tyagi V., Buddhi D. PCM thermal storage in buildings: A state of art. *Renewable and Sustainable Energy Reviews*.

- [24] Sharma A., Tyagi V.V., Chen C.R., Buddhi D. Review on thermal energy storage with phase change materials and applications. *Renewable and Sustainable Energy Reviews*, in press. Available online at www.sciencedirect.com
- [25] Koschenz M., Lehmann B. Development of a thermally activated ceiling panel with PCM for application in lightweight and retrofitted buildings. *Energy and Buildings* (2004) 36 (6):567–78.
- [26] Heine D. (1987). Corrosion behaviour of steels in contact with salt eutectics as latent heat storage materials. *Heat Recovery Systems & CHP Vol. 7, No. 4*, pp. 389-394.
- [27] Groll M., Brost O., Heine D. (1990). Corrosion of steels in contact with salt eutectics as latent heat storage materials: influence of water and other impurities. *Heat Recovery Systems & CHP Vol. 10, No. 5/6*, pp. 567-572.
- [28] Cabeza L.F., Illa J., Roca J., Badia F., Mehling H., Hiebler S., Ziegler F. (2001). Immersion corrosion tests on metal-salt hydrate pairs used for latent heat storage in the 32 to 36 °C temperature range. *Materials and Corrosion* 52, 140-146.
- [29] Cabeza L.F., Illa J., Roca J., Badia F., Mehling H., Hiebler S., Ziegler F. (2001). Middle term immersion corrosion tests on metal-salt hydrate pairs used for latent heat storage in the 32 to 36 °C temperature range. *Materials and Corrosion* 52, 748-754.
- [30] Cabeza L.F., Roca J., Nogués M., Mehling H., Hiebler S. (2002). Immersion corrosion tests on metal-salt hydrate pairs used for latent heat storage in the 48 to 58 °C temperature range. *Materials and Corrosion* 53, 902-907.
- [31] Nagano K., Ogawa K., Mochida Hayashi T.K., Ogoshi H. (2004). Performance of heat charge/discharge of magnesium nitrate hexahydrate and magnesium chloride hexahydrate mixture to a single vertical tube for a latent heat storage system. *Applied Thermal Engineering*, 24 209–220.
- [32] Cabeza L.F., Roca J., Nogués M., Mehling H., Hiebler S. (2005). Long term immersion corrosion tests on metal-PCM pairs used for latent heat storage in the 24 to 29 °C temperature range. *Materials and Corrosion*, 56, No. 1.
- [33] Sari A., Kaygusuz K. (2003). Some fatty acids used for latent heat storage: thermal stability and corrosion of metals with respect to thermal cycling. *Renewable Energy* 28 939–948.
- [34] Lázaro A., Zalba B., Bobi M., Castellón C., Cabeza L.F. (2005). Experimental Study on Phase Change Materials and Plastics Compatibility. *Environmental and energy engineering*. Published online September 15, 2005 in Wiley InterScience (www.interscience.wiley.com).
- [35] Cabeza L.F., Svensson G., Hiebler S., Mehling H. (2003). Thermal performance of sodium acetate trihydrate thickened with different materials as phase change energy storage material. *Applied Thermal Engineering* 23 1697–1704.
- [36] Sharma A., Sharma S.D., Buddhi D. (2002). Accelerated thermal cycle test of acetamide, stearic acid and paraffin wax for solar thermal latent heat storage applications. *Energy Conversion and Management* 43: 1923-1930.
- [37] Sharma S.D., Buddhi D., Sawhney R.L. (1998). Accelerated thermal cycle tests of industrial grade phase change materials. *Proc. National Solar Energy Convention-97: Towards Commercialization of Clean Energy*. Chennai. India. Anna University: 73-77.
- [38] Sharma S.D., Buddhi D., Sawhney R.L. (1999). Accelerated thermal cycle test of latent heat storage materials. *Solar Energy* 66: 483-490.
- [39] Fernanda G.P. (1988). Salt hydrates used for latent heat storage: corrosion metals and reliability of thermal performance. *Solar Energy* 41(2): 193–197.
- [40] Hadjieva M., Kanev S., Argirov J. (1992). Thermophysical properties of some paraffins applicable to thermal energy storage. *Solar Energy Mater. Solar Cells* 27 181–187.
- [41] Gibbs B.M., Hasnain S.M. (1995). DSC study of technical grade phase change heat storage materials for solar heating applications. *Proceedings of the 1995 ASME/JSME/JSEJ International Solar Energy Conference*. Part 2.
- [42] Costello Y.A., Melsheimer S.S., Edie D.D. (1978). Heat transfer and calorimetric studies of a direct contact-latent heat energy storage system; thermal storage and heat transfer in solar energy systems. *ASME Meeting, San Francisco, USA*, p. 10-15.
- [43] Edie D.D., Melsheimer S.S. (1976). An immiscible fluid-heat of fusion energy storage system. In: *Proceedings of Sharing the Sun: Solar Technology in the Seventies*. A Joint Conference of the

- American Section of the International Solar Energy Society and the Solar Energy Society of Canada Inc., Winnipeg. The American Section of the International Solar Energy Society, p. 227-237.
- [44] Fouda A.E., Despault G.J., Taylor J.B., Capes C.E. (1984). Solar storage system using salt hydrate latent heat and direct contact heat exchange – II, characteristics of pilot operating with sodium sulfate solution. *Solar Energy* 32, 57-65.
- [45] Farid M.M., Yacoub K. (1989). Performance of direct contact latent heat storage unit. *Solar Energy* 43, 237-252.
- [46] Farid M.M., Khalaf A.N. (1994). Performance of direct contact latent heat storage unit with two hydrated salts. *Solar Energy* 52, 179-189.
- [47] Ryu H.W., Woo S.W., Shin B.C., Kim S.D. (1992). Prevention of subcooling and stabilization of inorganic salt hydrates as latent heat storage materials. *Solar Energy Materials and Solar Cells* 27, 161-172.
- [48] Salyer O., Sircar A.K., Chartoff R.P., Miller D.E. (1985). Advanced phase-change materials for passive solar storage applications. In: *Proceedings of the 20th Intersociety Energy Conversion Engineering Conference*. Warrendale, Pennsylvania, USA (1985) 699-709.
- [49] Banu D., Feldman D., Haghighat F., Paris J., Hawes D. (1998). Energy-storing wallboard: Flammability tests. *Journal of materials in civil engineering*.
- [50] Salyer I.O., Sircar A.K. (1990). Phase change materials for heating and cooling of residential buildings and other applications. *Proceedings of the 25th intersociety energy conversion engineering conference*, 236-43.
- [51] Naumann R., Emons H.H. (1989). Results of thermal analysis for investigation of salt hydrates as latent heat-storage materials. *Journal of Thermal Analysis*; 35:1009–31.
- [52] Lane G.A. (1980). Low temperature heat storage with phase change materials. *International Journal of Ambient Energy*; 1: 155–68.
- [53] Li J.H., Zhang G.E., Wang J.Y. (1991). Investigation of a eutectic mixture of sodium acetate trihydrate and urea as latent heat storage. *Solar Energy*; 47(6): 443–5.
- [54] Zalba B., Marin J.M., Cabeza L.F., Harald M. (2004). Free cooling of buildings with phase change materials. *International Journal of Refrigeration* 27 (8) 839–849.
- [55] Feldman D., Shapiro M.M., Banu D. (1986). Organic phase change materials for thermal energy storage. *Solar Energy Mater*; 13: 1–10.
- [56] www.teappcm.com
- [57] www.epsltd.co.uk
- [58] www.rubitherm.de
- [59] www.climator.com
- [60] <http://www.deltams.com/bvf/ca-en/products/pcm/produkte/cool25.php>
- [61] Kakiuchi H. Mitsubishi Chemical Corporation, Private Communication, 2002.
- [62] www.cristopia.com
- [63] Speyer R.F. (1994). *Thermal Analysis of Materials*. Marcel Dekker, New York.
- [64] Eckert E.R.G., Goldstein R.J., Ibele W.E., Patankar S.V., Simon T.W., Strykowski P.J., Tamma K.K., Kuehn T.H., Bar-Cohen A., Heberlein J.V.R., Hofeldt D.L., Davidson J.H., Bischof J., Kulacki F. (1997). Heat transfer - a review of 1994 literature. *International Journal of Heat Trasfer* 40 3729–3804.
- [65] Zalba B. (2002). Almacenamiento térmico de energía mediante cambio de fase, Procedimiento experimental. Ph.D. Thesis, University of Zaragoza (Spain).
- [66] Kondo T., Ibamoto T. (2003). Research on using PCM for ceiling board. *Proceedings of the 9th International Conference on Thermal Energy Storage – Futurestock'2003*, Warsaw (Poland).
- [67] Takeda S., Nagano K., Mochida T., Shimakura K. (2004). Development of a ventilation system utilizing thermal energy storage for granules containing phase change material. *Solar Energy* 77, 329-338.
- [68] Turnpenny J.R., Etheridge D.W., Reay D.A. (2000) Novel ventilation cooling system for reducing air conditioning in buildings. Part I: testing and theoretical modelling. *Applied Thermal Engineering* 20, 1019-1037.

- [69] Inaba H., Tu P. (1997). Evaluation of thermophysical characteristics on shape-stabilized paraffin as a solid-liquid phase change material. *Heat Mass Transfer* 32 307–312.
- [70] Markux Y., Minevich A., Ben-Dor L. (2003) Differential drop calorimetry for the determination of enthalpy of fusion. *Journal of. Chemical. Thermodynamics* 35 1009–1018.
- [71] Zhang Y., Yi Y., Yi J. (1999). A simple method, the T-history method, of determining the heat of fusion, specific heat and thermal conductivity of phase-change materials. *Measurement Sci. Technol.* 10 201–205.
- [72] Lane G.A. (1989). Phase Change Thermal Storage Materials. In: *Hand Book of Thermal Design*. In: Guyer, C., ed. McGraw Hill Book Co.
- [73] Flaherty B. (1971). Characterisation of waxes by differential scanning calorimeter. *J Appl Chem Biotechnology*. 21: 144.
- [74] Cantor S. (1978). Applications of differential scanning calorimetry to the study of thermal energy storage. *Thermochemica Acta* 26(1–3): 39–47.
- [75] Elder J.P. (1980). Thermal energy storage materials - a DSC study. *Thermochemica Acta* 36(1): 67–77.
- [76] Bukovec N., Bukovec P., Arbanas V. (1989). TG and DSC investigation of $\text{CaCl}_2 \cdot 6\text{H}_2\text{O}$ a phase change material. *Thermochemica Acta* 148: 281–288.
- [77] Dunn J.G., Smith H.G., Willix R.L. (1989). The supercooling of acetamide. *Thermochemica Acta* 80: 343–353.
- [78] Aboul-Enein S., Olofa S.A. (1991). Thermophysical properties of heat-of-fusion storage materials for cooling applications. *Renewable Energy* 1(5 - 6): 791–797.
- [79] Takahashi Y., Neigishi A., Abe Y., Tanaka K., Kamimoto M. (1991). Thermoanalytical investigation of fluoride composites for latent thermal storage. *Thermochemica Acta* 183: 299–311.
- [80] Babich M.W., Hwang S.W., Mounts R.D. (1992). The search for novel energy storage materials using differential scanning calorimetry. *Thermochemica Acta* 210: 83–88.
- [81] Richardson M.J. (1993). The derivation of thermodynamic properties by DSC: free energy curves and phase stability. *Thermochemica Acta* 36 (1): 67–77.
- [82] Feldman D., Banu D. (1996). DSC analysis for the evaluation of an energy storing wallboard. *Thermochemica Acta* 272: 243–251.
- [83] Salmerón J.M. (2005). Caracterización de las técnicas de refrigeración natural con acumulación estructural. Potencial de ahorro energético en el acondicionamiento de edificios. Tesis Doctoral. Universidad de Sevilla. 224. ISBN: 84-689-7782-9.
- [84] Ruíz A. (2009). Ahorro energético mediante el uso de elementos de doble envolvente transparente-opaco. Tesis Doctoral. Universidad de Sevilla
- [85] Shilei L., Neng Z., Guohui F. (2006). Eutectic mixtures of capric acid and lauric acid applied in building wallboards for heat energy storage. *Energy and Buildings* 38: 708–711.
- [86] Yannas S., Erell E., Molina J.L. (2006). *Roof Cooling Techniques; A Design Handbook*. Earthscan, London, UK.
- [87] Zhang Y., Zhou G., Lin K., Zhang Q., Di H. (2007). Application of latent heat thermal energy storage in buildings: State-of-the-art and outlook. *Building and Environment* 42: 2197–2209.
- [88] Hong H., Kim S.K., Kim Y.S. (2004). Accuracy improvement of t-history method for measuring heat of fusion of various materials. *International Journal of Refrigeration* 27: 360–366.
- [89] Marín J.M., Zalba Z., Cabeza L.F., Mehling H. (2003). Determination of enthalpy-temperature curves of phase change materials with the temperature-history method: improvement to temperature dependent properties. *Measurement science and technology*. Published 7 January 2003. Online at stacks.iop.org/MST/14/184
- [90] Lázaro A., Günther E., Mehling H., Hiebler S., Marín J.M., Zalba B. (2006). Verification of a T-history installation to measure enthalpy versus temperature curves of phase change materials. *Measurement science and technology*. Published 13 July 2006 online at stacks.iop.org/MST/17/2168.
- [91] Pasupathy A., Velraj R., Seeniraj R.V. (2008). Phase change material-based building architecture for thermal management in residential and commercial establishments. *Renewable and Sustainable Energy Reviews* 12, 39–64.

- [92] Neeper D. (1990). Benefits of wallboard impregnated with phase-change materials for residential heating and cooling. Subcontract Report to Solar Energy Research Institute.
- [93] Stoval T.K., Tomlinson J.J. What are the potential benefits of including latent storage in common wallboard? *Trans ASME* 1995; 117:318–25.
- [94] Stetiu C., Feustel H.E. Phase change wallboard as an alternative to compressor cooling in Californian residences. In: *Proceedings of 96 ACEE Summer Study for Energy Efficient Building*, California, USA, 1996.
- [95] Nagano K., Takeda S., Mochida T., Shimakura K., Nakamura T. Study of a floor supply air conditioning system using granular phase change material to augment building mass thermal storage—Heat response in small scale experiments. *Energy and Buildings* 38 (2006) 436–446.
- [96] Halford C.K., Boehm R.F. (2007). Modelling of phase change material peak load shifting. *Energy and Buildings* 39 298–305.
- [97] Zhang M., Medina M.A., and King J.B. Development of a thermally enhanced frame wall with phase change materials for on-peak air conditioning demand reduction and energy savings in residential buildings. *Int. J. Energy Res.* 2005; 29:795–809.
- [98] Scalat S., Banu D., Hawes D., Paris J., Haghighata F., Feldman D. (1996). Full scale thermal testing of latent heat storage in wallboard. *Solar Energy Materials and Solar Cells* 44, 49-61.
- [99] Athienitis A.K., Liu C., Hawes D., Banu D., Feldman D. (1997). Investigation of the Thermal Performance of a Passive Solar Test-Room with Wall Latent Heat Storage. *Building and Environment*, Vol. 32, No. 5, pp. 405-410.
- [100] Fang X., Zhang Z. A novel montmorillonite-based composite phase change material and its applications in thermal storage building materials. *Energy and Buildings* 38 (2006) 377–380.
- [101] Schossig P., Henning H.M., Gschwander S., Haussmann T. Micro-encapsulated phase-change materials integrated into construction materials. *Solar Energy Materials & Solar Cells* 89 (2005) 297–306.
- [102] Ahmad M., Bontemps A., Sallée H., Quenard D. Experimental investigation and computer simulation of thermal behaviour of wallboards containing a phase change material. *Energy and Buildings* 38 (2006) 357–366.
- [103] Ahmad M., Bontemps A., Sallée H., Quenard D. (2006). Thermal testing and numerical simulation of a prototype cell using light wallboards coupling vacuum isolation panels and phase change material. *Energy and Buildings* 38, 673–681.
- [104] Hawes D.W., Feldman D. (1992). Absorption of phase change materials in concrete. *Solar Energy Materials and Solar Cells* 27 91-101.
- [105] Hawes D.W., Banu D., Feldman D. (1992). The stability of phase change materials in concrete. *Solar Energy Materials and Solar Cells* 27 103-118.
- [106] Hadjieva M., Stoykov R., Filipova Tz. (2000). Composite salt-hydrate concrete system for building energy storage. *Renewable Energy* 19 111±115.
- [107] Cabeza L.F., Castellón C., Nogués M., Medrano M., Leppers R., Zubillaga O. (2007) Use of microencapsulated PCM in concrete walls for energy savings. *Energy and Buildings* 39 113–119.
- [108] Lee T., Hawes D.W., Banu D., Feldman D. (2000). Control aspects of latent heat storage and recovery in concrete. *Solar Energy Materials* 62, 217-237.
- [109] Kudhair A.M. Use of phase change materials impregnated into building material for thermal energy storage applications. *New Zealand* June 2006.
- [110] Salyer I.O., Botham R.A., Jenkins G.H., Ball III G.L. Form-sTabla crystalline polymer pellets for thermal energy storage.
- [111] Salyer, I.O., Sircar A.K., Kumar A. Advanced phase change materials technology: evaluation in lightweight solite hollow-core building blocks. (1995). *Proceedings of the Intersociety Energy Conversion Engineering Conference* 2, pp. 217-224
- [112] Lamberg P., Jokisalo J., Sirén K. (2000). The effects on indoor comfort when using phase change materials with building concrete products. *Proceedings of Healthy Buildings 2000*, Vol. 2, pp. 751–756, SIY Indoor Air Information OY.
- [113] Castellón C. Use of Microencapsulated Phase Change Material in buildings. PhD thesis. GREA Innovació concurrent. University of Lleida, Spain.

- [114] Ibáñez M., Lázaro A., Zalba B., Cabeza L.F. (2005). An approach to the simulation of PCMs in building applications using TRNSYS. *Applied Thermal Engineering* 25, 1796–1807.
- [115] Pasupathy A., Velraj R. (2008). Effect of double layer phase change material in building roof for year round thermal management. *Energy and Buildings* 40, 193–203.
- [116] Mehling H., Krippner R., Hauer A. (2002) Research project on PCM in wood-lightweight-concrete. *Proceedings of the 2nd Workshop of IEA ECES IA Annex 17*, Ljubljana (Slovenia).
- [117] Carbonari A., Grassi M., Perna C., Principi P. (2006). Numerical and experimental analyses of PCM containing sandwich panels for prefabricated walls. *Energy and Buildings* 38, 472–483.
- [118] Alawadhi E.M. (2008). Thermal analysis of a building brick containing phase change material. *Energy and Buildings* 40, 351–357.
- [119] Stritih U., Butala V. Energy saving in building with PCM cold storage. *International Journal of Energy Research* 31 (2007) 1532-1544.
- [120] Arkar C., Vidrih B., Medved S. (2007). Efficiency of free cooling using latent heat storage integrated into the ventilation system of a low energy building. *International Journal of Refrigeration* 30, 134-143.
- [121] Arkar C., Vidrih B., Medved S, Numerical modelling of free cooling of low energy building utilizing PCM heat storage integrated into the ventilation system. *Eighth International IEA Workshop (Annex 17), Advanced Thermal Energy Storage Through Phase Change Materials and Chemical Reactions*, April 18e20, 2005, Kizkalesi, Mersin, Turkey, pp. 1e11, www.fskab.com/Annex17/.
- [122] Takeda S., Nagano K., Mochida T., Nakamura T. Development of floor supply air conditioning system with granulated phase change materials. *Proceedings of the 9th International Conference on Thermal Energy Storage – Futurestock’2003*, Warsaw (Poland) (2003).
- [123] Zukowski M. A numerical model of the air-underfloor heat exchanger. *Proceedings of the 9th International Conference on Thermal Energy Storage – Futurestock’2003*, Warsaw (Poland) (2003).
- [124] Pluta Z. Numerical analysis of pebble/PCM bed storage systems for solar air heating installations. *Proceedings of the 9th International Conference on Thermal Energy Storage – Futurestock’2003*, Warsaw (Poland) (2003).
- [125] Lin K., Zhang Y., Xu X., Di H., Yang R., Qin P. (2006). Experimental study of under-floor electric heating system with shape-stabilized PCM plates. *Energy and Buildings* 37 (3), 215–220.
- [126] Lin K., Zhang Y., Xu X., Di H., Yang R., Qin P. Modeling and simulation study of under-floor electric heating system with shape-stabilized PCM plates. *Building Environment* 39 (12), 1427–1434.
- [127] Xu X., Zhang Y., Lin K., Di H., Yang R. Modeling and simulation on the thermal performance of shape-stabilized phase change material floor used in passive solar buildings. *Energy and Buildings* 37 (2005) 1084–1091.
- [128] Ismail K.A.R., Salinas C.T., Henriquez J.R. Comparison between PCM filled glass windows and absorbing gas filled windows. *Energy and Buildings* 40 (2008) 710–719.
- [129] Ismail K.A.R., Enríquez J.R. Thermally effective windows with moving phase change materials curtains. *Applied Thermal Engineering* 21 (2001) 1909-1923.
- [130] Ismail K.A.R., Enríquez J.R. Performance of composite glass windows. *Proceedings Eurotherm Seminar n° 44 – Advances in Thermal Insulation*, Espinho-Porto, Portugal, 1995, pp. 219-230.
- [131] Ismail K.A.R., Enríquez J.R. Analysis of thermal and optical composite glass window. *Proceedings of the Second European Thermal-Sciences and 14th UIT National Heat Transfer Conference*. Rome, Italy, vol. 2, 1996, pp. 695-702.
- [132] Merker O., Hepp V., Beck A., Fricke J. (2002). A new PCM-shading system: a study of the thermal charging and discharging process. *Proceedings of Eurosun 2002*, Bologna (Italy).
- [133] Merker O., Hepp F., Beck A., Fricke J. (2002). A new solar shading system with phase change material (PCM). *Proceedings of the World Renewable Energy Congress WII*, Cologne (Germany).
- [134] Buddhi D., Sharma S.D. (1999). Measurements of transmittance of solar radiation through stearic acid: latent heat storage material. *Energy Convers Manage* 40, 1979–1984.
- [135] Pasupathy A., Athanasius L., Velraj R., Seeniraj R.V. Experimental investigation and numerical simulation analysis on the thermal performance of a building roof incorporating phase change material (PCM) for thermal management. *Applied Thermal Engineering* 28 (2008) 556–565.

- [136] Askew G.L. (1978). Solar heating utilization a paraffin's phase change material. In: Proceedings of the second national passive solar conference, Philadelphia, PA.
- [137] Farouk B., Guceri S.I. (1979). Tromb-Michal wall using a phase change material. In: Proceedings of the second Miami international conference on alternative energy, Miami.
- [138] Bourdeau L.E. (1980). Study of two passive solar systems containing phase change materials for thermal storage. In: Proceedings of 5th national passive solar conference, October 19–26, Amherst. Newark, Delaware: American Solar Energy Society, 297–301.
- [139] Swet C.J. (1980). Phase change storage in passive solar architecture. In: Proceedings of the 5th national passive solar conference, October 19–26, Amherst. Newark, Delaware: American Solar Energy Society, 282–286.
- [140] Ghoneim A.A., Klein S.A., Duffie J.A. (1991). Analysis of collector-storage building walls using phase-change-materials. *Solar Energy* Vol. 47, No. 3, pp. 237-242.
- [141] Chandra S., Kumar R., Kaushik S., Kaul S. (1985). Thermal performance of a non A/C building with PCCM thermal storage wall. *Energy Conversion and Management* 25 (1), 15–20.
- [142] Knowler T. (1983). Proportioning composites for efficient-TSWs. *Solar Energy* 31 (3), 319–326.
- [143] Castellón C., Medrano M., Roca J., Nogués M., Castell A., Cabeza L.F. (2007). Use of microencapsulated Phase Change Materials in building applications. Thermal Performance of the Exterior Envelopes of Whole Buildings X International Conference, December 2-7, 2007 Sheraton Sand Key Resort Clearwater Beach, Florida.
- [144] Feldman D., Banu D., Hawes D., Ghanbari E. (1991). Obtaining an energy storing building material by direct incorporation of an organic phase change material in gypsum wallboard. *Solar Energy Materials*; 22(2–3):231–42.
- [145] Eames I.W., Adref K.T. (2002). Freezing and melting of water in spherical enclosures of the type used in thermal (ice) storage systems. *Applied Thermal Engineering* 22, 733-745.
- [146] Bedecarrats J.P., Dumas J.P. (1997). Etude de la cristallisation de nodules contenant un materiau à changement de phase en vue du stockage par chaleur latent. *International Journal of Heat and Mass Transfer* 40, 149-157.
- [147] Bedecarrats J.P., Strub F., Falcon B., Dumas J.P. (1996). Phase-change thermal energy storage using spherical capsules: performance of a test plant. *International Journal of Refrigeration* 19, 187-196.
- [148] Alloncle R. (1983). Étude en régime périodique d'un accumulateur thermique à chaleur latente. Application à un matériau encapsulé. *Revue Générale de thermique Fr.* (254) (1983) 161-167.
- [149] Khudhair A.M., Farid M.M. (2004). A review on energy conservation in building applications with thermal storage by latent heat using phase change materials. *Energy Conversion and Management* 45 263–275.
- [150] Sharma S.D.; Sagara K. (2005). Latent Heat Storage Materials and Systems: A Review. *International Journal of Green Energy* Online Publication Date: 01 January 2005.
- [151] Zalba B., Marín J.M., Cabeza L.F., Mehling H. (2003). Review on thermal energy storage with phase change: materials, heat transfer analysis and applications. *Applied Thermal Engineering* 23 251–283.
- [152] Brown R.C., Rasberry J.D., Overmann S.P. (1998). Microencapsulated phase-change materials as heat transfer media in gas-fluidized beds. *Powder Technology* 98 (3) 217-222.
- [153] Hawlader M.N.A., Uddin M.S., Khin M.M. (2003). Microencapsulated PCM thermal-energy storage system. *Applied Energy* 74 195-202.
- [154] Özönur Y., Mazman M., Paksoy H.Ö., Evliya H. (2006). Microencapsulation of coco fatty acid mixture for thermal energy storage with phase change material. *International Journal of Energy Research*; 30: 741–749.
- [155] Jahns E. (1999). Microencapsulated phase change materials. Proceedings of the 4th IEA ECES IEA Annex 10 Workshop, Benediktbeuern (Germany).
- [156] Schossig P., Henning H.M., Haussman T., Raicu A. (2003). Encapsulated Phase-Change Materials integrated into construction materials. Proceedings of the 9th International Conference on Thermal Energy Storage – Futurestock'2003, Warsaw (Poland).

- [157] Castell A., Medrano M., Castellón C., Cabeza L.F. (2007). Demonstration cubicles to test PCM with different construction materials. IEA ECES IA Annex 20 3rd Workshop, Beijing (China).
- [158] Kedl R.J., Stovall T.K. (1989). Activities in support of the wax-impregnated wallboard concept: thermal energy storage researches activity review. U.S. Department of Energy, New Orleans, Louisiana, USA.
- [159] Kaasinen H. (1992). Absorption of phase change substances into commonly used building materials. *Solar Energy Materials and Solar Cells* 27 (2), 173–9.
- [160] Inaba H., Tu P. (1997). Evaluation of thermophysical characteristics on shapestabilized paraffin as a solid–liquid phase change material. *Heat and Mass Transfer* 32 (4) 307–312.
- [161] Ye H., Ge X.S. (2000). Preparation of polyethylene–paraffin compound as a formsTabla solid–liquid phase change material. *Solar Energy Materials & Solar Cells* 64 (1) 3744–3748.
- [162] Py X., Olives P., Mauran S. (2001). Paraffin/porous-graphite-matrix composite as a high and constant power thermal storage material. *Heat and Mass Transfer* 44 (14) 2727–2737.
- [163] Xiao M., Feng B., Gong K.C. (2002). Preparation and performance of shapestabilized phase change thermal storage materials with high thermal conductivity. *Energy Conversion & Management* 43 (1) 103–108.
- [164] Xiao M., Feng B., Gong K.C. (2001). Thermal performance of a high conductive shape-stabilized thermal storage material. *Solar Energy Materials & Solar Cells* 69 (3) 293–296.
- [165] Zhang Y.P., Lin K.P., Yang R., Di H.F., Jiang Y. (2006). Preparation, thermal performance and application of shape-stabilized PCM in energy efficient buildings. *Energy and Buildings* 38 1262–1269.
- [166] Xu X., Zhang Y.P., Lin K.P., Di H.F., Yang R. (2005). Model and simulation research on thermal performance of shape-stabilized phase change material floor. *Energy and Buildings* 37 (10) 1084–1091.
- [167] Zhang Y.P., Xu X., Di H.F., Lin K. Yang R. (2006). Experimental study on the thermal performance of the shape-stabilized phase change material floor used in passive solar buildings. *Journal of Solar Energy Engineering, Transactions of the ASME* 128 (2), pp. 255-257,
- [168] Lin K.P., Zhang Y.P., Xu X.H., Di H.F., Yang R. (2004). Modeling and simulation of underfloor electric heating system with shape-stabilized PCM plates. *Building and Environment* 39 1427–1434.
- [169] Lin K.P., Zhang Y.P. (2005). Experimental research of under-floor electric heating system with shape-stabilized PCM plates. *Energy and Building* 37 (3) 215–220.