

BIBLIOGRAFÍA

- [1] D. Leguillon, «Strength or toughness? A criterion for crack onset at a notch,» *European Journal of Mechanics*, nº 21, pp. 61-72, 2001.
- [2] T. C. T. Ting., *Anisotropic Elasticity*, Oxford Science Publications.
- [3] H. P. P. a. G. I. Tada, *The Stress Analysis of Cracks Handbook*, 3rd ed., New York: ASME Press, 2000, p. 696.
- [4] O. Bergsma, *Composites materials, structures and production processes*, DELF, 2013-14.
- [5] B. J. Aronsson CG, «Tensile fracture of laminates with cracks,» *Journal of Composite Materials*, nº 20, p. 287–307, 1986.
- [6] H. S. S. Z. F. B. Bao G, «The role of material orthotropy in fracture specimens for composites.,» *International Journal of Solids Structures*, nº 29, pp. 1015-1116, 1992.
- [7] C. G. Camanho PP, «On the relation between the composite laminate fracture toughness and that of the 0° ply fracture toughness: analytical model and experimental validation.,» *Engineering Fracture Mechanics*, nº 78, pp. 2535-2546, 2011.
- [8] N. C. O. E. M. D. Leguillon, «A coupled strength and toughness criterion for the prediction of the open hole tensile strength of a composite plate.,» *International Journal of Solids and Structures*, nº 49, p. 3915–3922, 2012.
- [9] G. E. G. C. S. M. P. L. P.P. Camanho, «A finite fracture mechanics for the prediction of the open-hole strength of composite laminates.,» *Composites: Part A*, nº 43, pp. 1219-1225, 2012.